

**CHCNAV**

**iBase**

**GNSS RECEIVER**



**SURVEYING  
& ENGINEERING**

# RUGGED INTEGRATED GNSS BASE RECEIVER

The iBase GNSS receiver is a fully integrated professional GNSS base station, specifically designed to meet 95% of surveyors' needs when working in UHF GNSS base and rover mode. The performance of the iBase UHF base station compared to a standard external UHF radio modem is almost perfect. But its unique design eliminates the need for a heavy external battery, cumbersome cables, external radio and radio antenna. Its 5-watt radio module provides operational GNSS RTK coverage up to 25 km with optimal conditions and features a real-time UHF interference self-checking technique, allowing the operator to select the most appropriate frequency channel to use.

## THE CONCEPT OF GNSS RTK STATION REDEFINED

**Start your projects in fractions of seconds.**

The iBase GNSS station is an all-in-one RTK GNSS station. No more cables or external batteries. No need to take many accessories, resulting in easier operation. The simplicity of the setup process improves work efficiency at least 3 times compared to conventional external radio solutions. Beyond a simple GNSS station, the iBase also includes a 4G modem for transmitting GNSS corrections via TCP/IP server. If connected to a RTK GNSS network, the iBase can be turned into a UHF repeater to broadcast RKT corrections to multiple rovers across a project site.

## INDUSTRIAL GRADE DESIGN

**Rugged conception for uninterrupted work.**

iBase is the GNSS base receiver that you can rely on regardless of your working environment. Its industrial design meets the stringent IP67 standard for water and dust ingress protection. The IK08 impact protection level further extends the life of the iBase GNSS receiver, allowing it to withstand accidental falls from the height of a tripod onto hard ground.

## LOWER CONSUMPTION, LONGER AUTONOMY, BROADER COVERAGE!

**Increased performance with 50% less power consumption.**

The iBase GNSS electronics design significantly reduces power needs without sacrificing the UHF modem's performance. Its two high-capacity removable batteries provide up to 12 hours of continuous operation when transmitting RTK corrections at 5 watts power output. With UHF coverage of up to 25 km in typical survey operations, and up to 5 km in difficult conditions such as wooded and suburban areas.

## BEST GNSS SIGNAL TRACKING IN ITS CLASS

**Full GNSS with 1408 channels and advanced multipath mitigation.**

The state-of-the-art 1408-channel GNSS technology leverages GPS, GLONASS, Galileo and BeiDou. The iBase GNSS integrates cutting-edge GNSS antenna technology and multipath mitigation algorithms to ensure that the highest quality GNSS corrections are transmitted to the GNSS rovers. The iBase outputs standard DGSS corrections in RTCM 3.x format for optimal performance. Internal 8 GB memory is available to store GNSS raw data for post-processing or quality control at a later stage.



**INTEGRATED  
GNSS BASE  
RECEIVER**



**BOOST PRODUCTIVITY OF  
GNSS BASE + ROVER SURVEY.**

---



# SPECIFICATIONS

| GNSS Performance <sup>(1)</sup>  |   |
|----------------------------------|---|
| Channels                         | 1408 channels   |
| GPS                              | L1C, A, L2P (Y), L2C, L5  |
| GLONASS                          | L1, L2  |
| Galileo                          | E1, E5a, E5b, E6*   |
| BeiDou                           | B1I, B2I, B3I, B1C, B2a, B2b  |
| QZSS                             | L1, L2, L5, L6*   |
| PPP                              | B2b-PPP   |
| SBAS                             | L1, L5  |
| GNSS Accuracies <sup>(2)</sup>   |   |
| Real time kinematics (RTK)       | Horizontal: 8 mm + 1 ppm RMS<br>Vertical: 15 mm + 1 ppm RMS<br>Initialization time: < 10 s<br>Initialization reliability: > 99.9% |
| Post-processing kinematics (PPK) | Horizontal: 3 mm + 1 ppm RMS<br>Vertical: 5 mm + 1 ppm RMS  |
| Post-processing static           | Horizontal: 2.5 mm + 0.5 ppm RMS<br>Vertical: 5 mm + 0.5 ppm RMS  |
| Code differential                | Horizontal: 0.4 m RMS<br>Vertical: 0.8 m RMS  |
| Autonomous                       | Horizontal: 1 m RMS<br>Vertical: 1.5 m RMS  |
| Positioning rate                 | Up to 10 Hz   |
| Time to first fix <sup>(3)</sup> | Cold start: < 45 s<br>Hot start: < 30 s<br>Signal re-acquisition: < 2 s   |
| Hardware                         |   |
| Size (L x W x H)                 | Φ160.5 mm x 103 mm<br>(Φ 6.32 in × 4.06 in)   |
| Weight                           | 1.73 kg (3.81 lb)   |
| Environment                      | Operating: -40°C to +65°C<br>(-40°F to +149°F)<br>Storage: -40°C to +85°C<br>(-40°F to +185°F)                                    |
| Humidity                         | 100% condensation   |
| Ingress protection               | IP67 waterproof and dustproof, protected from temporary immersion to depth of 1 m   |
| Shock                            | Survive a 2-meter pole drop   |
| Tilt sensor                      | E-Bubble leveling   |
| Front panel                      | 2 LED<br>0.96" OLED Display   |
| Certifications                   |   |

NGS Antenna Calibration

| Communication                                     |   |
|---|---|
| Network modem (optional)                          | Integrated 4G modem<br>LTE (FDD): B1, B2, B3, B4, B5, B7, B8, B20<br>DC - HSPA+/HSPA+/HSPA/UMTS:<br>B1, B2, B5, B8<br>EDGE/GPRS/GSM 850/900/1800/1900 MHz   |
| Wi-Fi   | 802.11 b/g/n, access point mode   |
| Bluetooth <sup>®</sup>                            | v 4.1   |
| Others  | NFC   |
| Ports   | 1 x 7-pin LEMO port (external power, RS-232)<br>1 x UHF antenna port (TNC female)   |
| UHF radio <sup>(4)</sup> (optional)               | Standard Internal Rx/Tx: 450 - 470 MHz<br>Transmit Power: up to 5 W<br>Protocol: CHC, Transparent, TT450,<br>Link rate: 9,600 bps / 19,200 bps<br>Range: Typical 5 km to 8 km,<br>up to 25 km with optimal conditions |
| Data formats                                      | RTCM2.x, RTCM3.x, CMR input / output<br>HCN, HRC, RINEX2.11, 3.02<br>NMEA 0183 output<br>NTRIP Client, NTRIP Caster   |
| Data storage                                      | 8 GB memory   |
| Electrical  |   |
| Power consumption                                 | 12 W (depending on user settings)   |
| Li-ion battery capacity                           | 2 x 7000 mAh, 7.4 V   |
| Operating time on internal battery <sup>(5)</sup> | UHF receive / transmit (5 W): 8 h to 12 h<br>Static: up to 15 h   |
| External power input                              | 9 V DC to 28 V DC   |

\*All specifications are subject to change without notice.

(1) Compliant, but subject to availability of BDS ICD and Galileo commercial service definition. Galileo E6 and QZSS L6 will be provided through future firmware upgrade. (2) Accuracy and reliability are determined under open sky, free of multipaths, optimal GNSS geometry and atmospheric condition. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (3) Typical observed values. (4) The use of UHF datalink may be subject to local regulations. Users must ensure that the device is not operated without the permission of the local authorities on frequencies or power output other than those specifically reserved and intended for use without required permit. (5) Battery life is subject to operating temperature.

© 2022 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision November 2022.

WWW.CHCNAV.COM | MARKETING@CHCNAV.COM

CHC Navigation Headquarter  
Shanghai Huace Navigation Technology Ltd.  
599 Gaojing Road, Building D,  
Shanghai, 201702, China,  
+86 21 54260273

CHC Navigation Europe  
Infopark Building, Sétány 1, 1117  
Budapest, Hungary  
+36 20 235 8248 +36 20 5999 369  
info@chcnv.eu

CHC Navigation USA LLC  
6380 S. Valley View Blvd Suite 246  
Las Vegas, NV 89118 USA  
+1 480 399 9533

CHC Navigation India  
409 Trade Center, Khokhra Circle,  
Maninagar East, Ahmedabad,  
Gujarat, India  
+91 90 99 98 08 02